

TYPHOON USB2.0 FRONT ACCESS HUB

Introduction

Increase your productivity with a single upgrade which comes with 9-in-1 Card Readers, USB ports, Firewire (IEEE 1394) port, Mic IN, Line IN, Video jacks, and Headset Out connections. All in a single 5.25" front panel for immediate and easy access in front of the computer. Everything at the back is now conveniently in front. No need to reach right to the back connections at the back of the computer anymore. Use the Typhoon USB2.0 Front Access Hub and operate your tasks directly and conveniently. Comes with 9-in-1 card readers for your Digital memory cards data transfers. Direct USB ports for your USB devices, and the Firewire port for your Digital Video device connections. 2 LEDs for power and activity status indications. Connect your keyboard and mouse from the front too.



Article Number: 83055

Features

- Four sockets support Secure Digital Card, Multi Media Card, Memory Stick, Smart Media Card, Memory Stick Pro, Compact Flash I/II Card, IBM Micro drive, and XD Card
- 1 x 1394 port & 2 x USB 2.0 ports
- 3 x jacks for mic, line-in & earphones
- 1 x RS-232 serial adapter, 2 x PS/2 ports, 2 x Video jacks. Internal design fit into 5.25" drive bay to save the desktop space
- Data exchange in different sockets within the readers
- Support USB High-Speed (480Mbps) or Full-speed (12Mbps) standards
- Active LED indicators for power and busy (read/write) status
- Supports Mass Storage Class Drive; no additional device driver needed under Windows® ME/XP Supports Windows® 98SE / 2000 / ME / XP or later

Specifications Function

- - Supports 8-512MB Secure Digital Card
- - Supports 8-512MB MMC Card
- - Supports 4-512MB MS Card
- - Supports 4-512MB MS-Pro Card
- - Supports 4-128MB Smart Media Card
- - Supports 4-512MB Compact Flash I/II Card
- - Supports 4-256MB XD Card
- - Supports 340MB / 512MB / 1.2GB IBM Micro drive
- - Supports Hot-Swapping
- USB transfer rates: High-Speed 480MB/Sec or

Full-Speed at 12MB/sec.

Card Data transfer rates: 700~4000Kb/s Max.

Socket

- - CF/MD socket
- - SD/MMC socket
- - MS socket
- - SM/XD socket
- Audio Jacks x 3 (mic , line-in , earphones)
- 1394 connector
- 2 x USB connectors
- RS-232 connector
- 2 x Video connectors (video in / out)
- 2 x PS/2 connector (keyboard / mouse)

Interface

Internal USB Rev. 2.0 / 1.1. device

Power

- DC +5.0V / +12.0V from PC PACKING
- DOCKING PANEL Cable (Internal cable x 1 & External cable x 1) Driver CD (User Manual)
- Y-cable DOCKING PANEL on one PCI slot metal bracket

System Requirements

- Intel® Pentium® III or above
- Windows® 98SE / ME / 2000 / XP or later
- USB port
- 1394 port
- Two video ports
- Three audio ports
- Two PS/2 ports
- One RS-232 port
- System with one PCI slot bracket access for the cables
- One available 5.25" bay